



Master-PUR H EL

Article Master No.: 000075

PU Suction & Transport Hose, medium duty, very flexible, electroconductive



antistatic



electrically
conductive



flexible



medium heavy



pressure
resistant

Product Details

Construction / Material

- Type of construction: profile extruded hose with metal spiral
- Spiral Design: made of steel wire
- Material of the spiral: spring steel
- Execution of the wall: made of electrically conductive material, wall thickness between the spirals approx. 1.4 mm
- Material of the wall: polyester polyurethane
- Specifications of the wall: surface resistance $R_0 < 10^3 \text{ Ohm}$

Properties

- Specifications of the product: complies with DIN 26057 Type III, according to TRGS 727 and ATEX 2014/34 EU
- Chemical Properties: halogen-free, good resistance to chemicals, good UV resistance, good resistance to oil, good resistance to petrol, good ozone resistance
- Flexibility: flexible
- Weight: medium heavy
- Pressure Resistance: pressure resistant
- Colour: black
- Other: high vacuum and good pressure resistance, configurable as a hose system with digital interface for compatibility with the AMPIUS® app

Operating Temperature

- Temperature Range: -40 to 90 °C
- short-term maximum temperature: peaks to 125 °C

Delivery Information

- Delivery, type of production: various nominal diameters in standard lengths are available ex-production, individual nominal diameters and lengths also ex-stock

Application Areas

- Areas of application: Bulk & Construction, Chemistry, Surface Technology, Food & Pharma, Plastics

Customizing Options

- optional item modification (on request): other nominal widths, with customer-specific imprint

Article Variants

Extended Article Number	Nominal Size (DN) in mm	Outer diameter in mm	Bending radius* in mm	Weight in kg/m	Operating pressure in bar	Negative pressure in bar	Max. Production length in m	Stock Lengths in m	Length (standard lengths available for order) in m
000075:25:x	25	32	46	0.28	4.17	0.92	25.00	/	5 / 10 / 15 / 20 / 25
000075:26:x	26	33	47	0.29	4.16	0.92	25.00	/	5 / 10 / 15 / 20 / 25
000075:32:x	32	41	60	0.39	3.25	0.92	25.00	5	5 / 10 / 15 / 20 / 25
000075:38:x	38	47	69	0.46	3.12	0.82	25.00	/	5 / 10 / 15 / 20 / 25
000075:40:x	40	49	72	0.49	3.00	0.82	25.00	5 / 10	5 / 10 / 15 / 20 / 25
000075:45:x	45	55	80	0.55	2.95	0.81	25.00	/	5 / 10 / 15 / 20 / 25
000075:51:x	51	61	87	0.71	2.90	0.79	25.00	5 / 10	5 / 10 / 15 / 20 / 25
000075:55:x	55	65	95	0.77	2.75	0.76	25.00	/	5 / 10 / 15 / 20 / 25
000075:60:x	60	70	102	0.84	2.55	0.74	25.00	5 / 10	5 / 10 / 15 / 20 / 25
000075:65:x	65	75	112	0.91	2.40	0.66	25.00	/	5 / 10 / 15 / 20 / 25
000075:70:x	70	80	117	0.97	2.25	0.66	25.00	/	5 / 10 / 15 / 20 / 25
000075:76:x	76	87	126	1.06	2.00	0.59	25.00	/	5 / 10 / 15 / 20 / 25
000075:80:x	80	91	132	1.11	2.00	0.59	25.00	/	5 / 10 / 15 / 20 / 25
000075:90:x	90	101	149	1.25	1.65	0.52	25.00	/	5 / 10 / 15 / 20 / 25
000075:102:x	102	112	165	1.48	1.50	0.44	25.00	5 / 10	5 / 10 / 15 / 20 / 25
000075:110:x	110	121	179	1.61	1.35	0.44	25.00	/	5 / 10 / 15 / 20 / 25
000075:115:x	115	126	186	1.68	1.35	0.31	25.00	/	5 / 10 / 15 / 20 / 25
000075:120:x	120	131	194	1.75	1.30	0.31	25.00	/	5 / 10 / 15 / 20 / 25
000075:127:x	127	139	205	1.91	1.30	0.31	25.00	/	5 / 10 / 15 / 20 / 25
000075:130:x	130	141	209	1.96	1.30	0.31	25.00	/	5 / 10 / 15 / 20 / 25
000075:140:x	140	151	224	2.11	1.05	0.25	25.00	/	5 / 10 / 15 / 20 / 25
000075:152:x	152	163	242	2.29	1.05	0.25	25.00	/	5 / 10 / 15 / 20 / 25
000075:160:x	160	171	255	2.51	0.90	0.25	25.00	/	5 / 10 / 15 / 20 / 25
000075:170:x	170	181	270	2.67	0.90	0.18	25.00	/	5 / 10 / 15 / 20 / 25
000075:180:x	180	191	285	2.82	0.75	0.18	25.00	/	5 / 10 / 15 / 20 / 25
000075:203:x	203	215	321	3.50	0.75	0.18	25.00	/	5 / 10 / 15 / 20 / 25
000075:225:x	225	237	353	3.65	0.60	0.12	25.00	/	5 / 10 / 15 / 20 / 25
000075:250:x	250	259	385	3.84	0.60	0.12	25.00	/	5 / 10 / 15 / 20 / 25
000075:254:x	254	263	390	3.84	0.60	0.12	25.00	/	5 / 10 / 15 / 20 / 25

Extended Article Number	Nominal Size (DN) in mm	Outer diameter in mm	Bending radius* in mm	Weight in kg/m	Operating pressure in bar	Negative pressure in bar	Max. Production length in m	Stock Lengths in m	Length (standard lengths available for order) in m
000075:275:x	275	288	426	4.22	0.45	0.12	25.00	/	5 / 10 / 15 / 20 / 25
000075:280:x	280	293	435	4.30	0.45	0.12	25.00	/	5 / 10 / 15 / 20 / 25
000075:300:x	300	313	465	4.94	0.45	0.12	20.00	/	5 / 10 / 15 / 20
000075:315:x	315	328	488	5.19	0.45	0.12	20.00	/	5 / 10 / 15 / 20
000075:325:x	325	338	503	5.35	0.45	0.12	20.00	/	5 / 10 / 15 / 20
000075:350:x	350	363	540	6.96	0.45	0.12	20.00	/	5 / 10 / 15 / 20
000075:375:x	375	388	580	7.45	0.30	0.07	20.00	/	5 / 10 / 15 / 20
000075:400:x	400	413	615	7.95	0.30	0.07	10.00	/	5 / 10 / 15 / 20
000075:450:x	450	463	690	8.94	0.30	0.07	10.00	/	5 / 10 / 15 / 20
000075:500:x	500	513	765	9.93	0.30	0.07	10.00	/	5 / 10 / 15 / 20

All data refer to a medium and ambient temperature of +20°C.
Specification of the bending radius related to the inside of the hose bend
Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

Suitable for the product



Master-Grip Hose Clamp, screwable
Special clamp for fastening light and medium-weight, right-handed spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO



Master-Grip Hose Clamp, screwable, Steel quality W4, stainless steel 1.4301
Special clamp for fastening light and medium-weight, right-handed spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO



Master-Grip Quick-Fix Clamp
Special clamp for fastening light and medium-weight, right-hand spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO




Hose connector
Sheet steel connector for extending, connecting and joining light to medium-weight hoses



Combiflex PU Screw Cuff EC
PU end fitting for Master-PUR L/H and Master-PVC L/H hoses, electrically conductive



Combiflex PU Threaded Sockets
PU threaded connector for all Master-PUR L, Master-PUR H and Master-PUR HX hose types, based on DIN ISO 228



Individual consultation

We offer consultation by phone: **+49 209 97077 0**

Product requests via: <https://www.masterflex.it/>

Headquarters for your sales area

Masterflex SE

Willy-Brandt-Allee 300
45891 Gelsenkirchen
Germany