



Master-PUR HÜ Trivolution

Article Master No.: 000150

PU Suction & Transport Hose, flexible, medium duty / reinforced, antistatic, microbe-resistant, hardly inflammable acc. to DIN 4102 B1



antistatic



microbe
resistant



flame retardant



transparent



moderately
flexible



heavy



pressure
resistant

Product Details

Construction / Material

- Type of construction: profile extruded hose with metal spiral
- Spiral Design: made of steel wire
- Material of the spiral: spring steel
- Execution of the wall: made of pure material, made of specified material, addition of a non-migrating permanent antistatic agent, wall thickness between the spirals approx. 1.7 mm
- Material of the wall: polyester polyurethane
- Specifications of the wall: surface resistance $R_0 < 10^9$ Ohm, measured according to DIN EN ISO 8031, material is more abrasion resistant than comparable polyurethane according to DIN ISO 4649, flame retardant according to DIN 4102 B1

Properties

- Specifications of the product: according to TRGS 727 and ATEX 2014/34 EU
- Chemical Properties: microbe-resistant, halogen-free, good resistance to chemicals, good UV resistance, good resistance to oil, good resistance to petrol, good ozone resistance, plasticiser-free
- Flexibility: moderately flexible
- Physical Properties: permanently antistatic
- Weight: heavy

- Pressure Resistance: pressure resistant
- Colour: transparent

Operating Temperature

- Temperature Range: -40 to 90 °C
- short-term maximum temperature: peaks to 125 °C

Delivery Information

- Delivery, type of production: various nominal diameters in standard lengths are available ex-production, individual nominal diameters and lengths also ex-stock

Application Areas

- Areas of application: Bulk & Construction, Chemistry, Food & Pharma, Waste Disposal & Cleaning Technology, Plastics

Article Variants

Extended Article Number	Nominal Size (DN) in mm	Outer diameter in mm	Bending radius* in mm	Weight in kg/m	Operating pressure in bar	Negative pressure in bar	Max. Production length in m	Stock Lengths in m
000150:102:x	102	111	187	1.72	1.77	0.62	25.00	/
000150:127:x	127	137	230	2.18	1.54	0.43	25.00	10
000150:152:x	152	162	275	2.38	1.26	0.36	25.00	/

All data refer to a medium and ambient temperature of +20°C.
Specification of the bending radius related to the inside of the hose bend
Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

Suitable for the product



Master-Grip Hose Clamp, screwable

Special clamp for fastening light and medium-weight, right-handed spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO



Master-Grip Hose Clamp, screwable, Steel quality W4, stainless steel 1.4301

Special clamp for fastening light and medium-weight, right-handed spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO



Master-Grip Quick-Fix Clamp

Special clamp for fastening light and medium-weight, right-hand spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO



Hose connector

Sheet steel connector for extending, connecting and joining light to medium-weight hoses




Hose Clamp with Bolts

special clamp for fastening medium and heavy spiral hoses to connection pipes on mobile and stationary units



Hose Clamp with Bolts, Steel quality W4, stainless steel 1.4301

Special clamp for fastening medium and heavy spiral hoses to connection pipes on mobile and stationary units



Individual consultation

We offer consultation by phone: **+49 209 97077 0**

Product requests via: <https://www.masterflex.it/>

Headquarters for your sales area

Masterflex SE

Willy-Brandt-Allee 300
45891 Gelsenkirchen
Germany