



Master-PUR L MHR

Article Master No.: 000010

PU Suction & Transport Hose, lightweight, microbe & hydrolysis-resistant



hydrolysis
resistant



microbe
resistant



transparent



flexible



light



moderately
pressure
resistant

Product Details

Construction / Material

- Type of construction: profile extruded hose with metal spiral
- Spiral Design: made of steel wire
- Material of the spiral: spring steel
- Execution of the wall: made of pure material, wall thickness between the spirals approx. 0.7 mm
- Material of the wall: polyether polyurethane

Properties

- Specifications of the product: complies with DIN 26057 Type II
- Chemical Properties: microbe-resistant, halogen-free, good resistance to chemicals, good UV resistance, good resistance to oil, good resistance to petrol, good ozone resistance, hydrolysis resistant, plasticiser-free
- Flexibility: flexible
- Weight: light
- Pressure Resistance: moderately pressure resistant
- Colour: transparent

Operating Temperature

- Temperature Range: -40 to 90 °C

- short-term maximum temperature: peaks to 125 °C

Application Areas

- Areas of application: Agriculture, Industry, aviation technology, Bulk & Construction, Sea & Rail transport, Chemistry, Food & Pharma, Waste Disposal & Cleaning Technology, Textile, Printing & Paper, Vehicle Construction

Customizing Options

- optional item modification (on request): other colours, other lengths, other nominal widths, with customer-specific imprint

Article Variants

Extended Article Number	Nominal Size (DN) in mm	Outer diameter in mm	Bending radius* in mm	Weight in kg/m	Operating pressure in bar	Negative pressure in bar	Max. Production length in m	Stock Lengths in m	Length (standard lengths available for order) in m
000010:25:x	25	30	30	0.24	3.22	0.79	25.00	/	5 / 10 / 15 / 20 / 25
000010:26:x	26	31	31	0.25	3.22	0.79	25.00	/	5 / 10 / 15 / 20 / 25
000010:32:x	32	40	40	0.35	2.52	0.71	25.00	/	5 / 10 / 15 / 20 / 25
000010:38:x	38	46	46	0.39	2.10	0.66	25.00	/	5 / 10 / 15 / 20 / 25
000010:40:x	40	48	48	0.40	2.10	0.66	25.00	/	5 / 10 / 15 / 20 / 25
000010:45:x	45	53	53	0.42	1.84	0.59	25.00	/	5 / 10 / 15 / 20 / 25
000010:51:x	51	58	58	0.45	1.68	0.52	25.00	/	5 / 10 / 15 / 20 / 25
000010:55:x	55	63	63	0.51	1.54	0.44	25.00	/	5 / 10 / 15 / 20 / 25
000010:60:x	60	68	68	0.53	1.40	0.44	25.00	/	5 / 10 / 15 / 20 / 25
000010:65:x	65	73	73	0.64	1.26	0.37	25.00	/	5 / 10 / 15 / 20 / 25
000010:70:x	70	78	78	0.68	1.12	0.37	25.00	/	5 / 10 / 15 / 20 / 25
000010:76:x	76	84	84	0.72	1.12	0.29	25.00	/	5 / 10 / 15 / 20 / 25
000010:80:x	80	88	88	0.76	0.98	0.29	25.00	/	5 / 10 / 15 / 20 / 25
000010:90:x	90	99	99	0.88	0.84	0.22	25.00	/	5 / 10 / 15 / 20 / 25
000010:102:x	102	110	110	0.95	0.84	0.22	25.00	/	5 / 10 / 15 / 20 / 25
000010:110:x	110	119	119	1.03	0.70	0.22	25.00	/	5 / 10 / 15 / 20 / 25
000010:115:x	115	124	124	1.06	0.70	0.22	25.00	/	5 / 10 / 15 / 20 / 25
000010:120:x	120	129	129	1.12	0.70	0.22	25.00	/	5 / 10 / 15 / 20 / 25
000010:127:x	127	135	135	1.18	0.70	0.22	25.00	/	5 / 10 / 15 / 20 / 25
000010:130:x	130	139	139	1.20	0.56	0.22	25.00	/	5 / 10 / 15 / 20 / 25
000010:150:x	150	159	159	1.46	0.56	0.15	25.00	/	5 / 10 / 15 / 20 / 25
000010:160:x	160	170	170	1.74	0.56	0.15	25.00	/	5 / 10 / 15 / 20 / 25
000010:170:x	170	180	180	1.80	0.42	0.15	25.00	/	5 / 10 / 15 / 20 / 25
000010:180:x	180	190	190	1.90	0.42	0.15	25.00	/	5 / 10 / 15 / 20 / 25
000010:203:x	203	214	214	2.30	0.42	0.15	25.00	5 / 10	5 / 10 / 15 / 20 / 25
000010:225:x	225	235	235	2.55	0.28	0.07	25.00	/	5 / 10 / 15 / 20 / 25
000010:250:x	250	260	260	3.02	0.28	0.07	25.00	/	5 / 10 / 15 / 20 / 25
000010:254:x	254	264	264	3.02	0.28	0.07	25.00	/	5 / 10 / 15 / 20 / 25
000010:275:x	275	284	284	3.11	0.28	0.07	25.00	/	5 / 10 / 15 / 20 / 25
000010:280:x	280	290	290	3.14	0.28	0.07	25.00	/	5 / 10 / 15 / 20 / 25
000010:300:x	300	310	310	3.20	0.25	0.07	20.00	/	5 / 10 / 15 / 20
000010:315:x	315	325	325	3.32	0.25	0.07	20.00	/	5 / 10 / 15 / 20

Extended Article Number	Nominal Size (DN) in mm	Outer diameter in mm	Bending radius* in mm	Weight in kg/m	Operating pressure in bar	Negative pressure in bar	Max. Production length in m	Stock Lengths in m	Length (standard lengths available for order) in m
000010:325:x	325	335	335	3.40	0.25	0.07	20.00	/	5 / 10 / 15 / 20
000010:350:x	350	360	360	3.60	0.13	0.07	20.00	/	5 / 10 / 15 / 20
000010:375:x	375	386	386	3.85	0.13	0.05	20.00	/	5 / 10 / 15 / 20
000010:400:x	400	411	410	4.45	0.13	0.05	20.00	/	5 / 10 / 15 / 20
000010:450:x	450	461	460	5.06	0.13	0.05	20.00	/	5 / 10 / 15 / 20
000010:500:x	500	511	510	5.70	0.13	0.05	20.00	/	5 / 10 / 15 / 20

All data refer to a medium and ambient temperature of +20°C.
Specification of the bending radius related to the inside of the hose bend
Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

Suitable for the product



Master-Grip Hose Clamp, screwable
Special clamp for fastening light and medium-weight, right-handed spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO



Master-Grip Hose Clamp, screwable, Steel quality W4, stainless steel 1.4301
Special clamp for fastening light and medium-weight, right-handed spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO



Master-Grip Quick-Fix Clamp
Special clamp for fastening light and medium-weight, right-hand spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO




Hose connector
Sheet steel connector for extending, connecting and joining light to medium-weight hoses



Combiflex PU Screw Cuff EC
PU end fitting for Master-PUR L/H and Master-PVC L/H hoses, electrically conductive



Combiflex PU Threaded Sockets
PU threaded connector for all Master-PUR L, Master-PUR H and Master-PUR HX hose types, based on DIN ISO 228



Individual consultation

We offer consultation by phone: **+49 209 97077 0**

Product requests via: <https://www.masterflex.it/>

Headquarters for your sales area

Masterflex SE

Willy-Brandt-Allee 300
45891 Gelsenkirchen
Germany