




Master-PVC L

Article Master No.: 000225

PVC Suction hose & Transport hose, light duty, highly flexible



microbe
resistant



hydrolysis
resistant



flexible



light



moderately
pressure
resistant

Product Details

Construction / Material

- Type of construction: profile extruded hose with metal spiral
- Spiral Design: made of steel wire
- Material of the spiral: spring steel
- Execution of the wall: wall thickness between the spirals approx. 0.7 mm
- Material of the wall: soft PVC

Properties

- Specifications of the product: according to TRGS 727 and ATEX 2014/34 EU, RoHS-compliant
- Chemical Properties: good resistance to oil, good resistance to chemicals, good resistance to alkaline solutions, good resistance to acids
- Flexibility: flexible
- Weight: light
- Pressure Resistance: moderately pressure resistant
- Colour: grey

Operating Temperature

- Temperature Range: -20 to 70 °C
- short-term maximum temperature: peaks to 80 °C

Delivery Information

- Delivery, type of production: various nominal diameters in standard lengths are available ex-production, individual nominal diameters and lengths also ex-stock

Application Areas

- Areas of application: Automotive, Plant & Mechanical Engineering, Robotics & Automation, Ventilation & Air-conditioning, Bulk & Construction, Chemistry, Food & Pharma, Plastics, Conveying, lifting & feeding technology, Cable manufacturers

Customizing Options

- optional item modification (on request): other colours, other lengths, other nominal widths, with customer-specific imprint

Article Variants

Extended Article Number	Nominal Size (DN) in mm	Outer diameter in mm	Bending radius* in mm	Weight in kg/m	Operating pressure in bar	Negative pressure in bar	Max. Production length in m	Stock Lengths in m	Length (standard lengths available for order) in m
000225:38:x	38	46	46	0.41	0.84	0.66	25.00	/	5 / 10 / 15 / 20 / 25
000225:40:x	40	48	48	0.42	0.84	0.66	25.00	/	5 / 10 / 15 / 20 / 25
000225:45:x	45	53	53	0.44	0.74	0.59	25.00	/	5 / 10 / 15 / 20 / 25
000225:50:x	50	57	57	0.47	0.68	0.53	25.00	/	5 / 10 / 15 / 20 / 25
000225:51:x	51	58	58	0.48	0.67	0.52	25.00	5 / 10	5 / 10 / 15 / 20 / 25
000225:55:x	55	63	63	0.54	0.62	0.44	25.00	/	5 / 10 / 15 / 20 / 25
000225:60:x	60	68	68	0.56	0.56	0.44	25.00	10	5 / 10 / 15 / 20 / 25
000225:65:x	65	73	73	0.68	0.50	0.37	25.00	/	5 / 10 / 15 / 20 / 25
000225:70:x	70	78	78	0.72	0.45	0.37	25.00	/	5 / 10 / 15 / 20 / 25
000225:75:x	75	83	83	0.75	0.45	0.30	25.00	/	5 / 10 / 15 / 20 / 25
000225:76:x	76	84	84	0.76	0.45	0.29	25.00	10	5 / 10 / 15 / 20 / 25
000225:80:x	80	88	88	0.80	0.39	0.29	25.00	10	5 / 10 / 15 / 20 / 25
000225:90:x	90	99	99	0.93	0.34	0.22	25.00	/	5 / 10 / 15 / 20 / 25
000225:100:x	100	108	108	0.99	0.34	0.22	25.00	/	5 / 10 / 15 / 20 / 25
000225:102:x	102	110	110	1.00	0.34	0.22	25.00	5 / 10	5 / 10 / 15 / 20 / 25
000225:110:x	110	119	119	1.09	0.28	0.22	25.00	/	5 / 10 / 15 / 20 / 25
000225:115:x	115	124	124	1.12	0.28	0.22	25.00	/	5 / 10 / 15 / 20 / 25
000225:120:x	120	129	129	1.18	0.28	0.22	25.00	/	5 / 10 / 15 / 20 / 25
000225:125:x	125	133	133	1.23	0.28	0.22	25.00	/	5 / 10 / 15 / 20 / 25
000225:127:x	127	135	135	1.25	0.28	0.22	25.00	/	5 / 10 / 15 / 20 / 25
000225:130:x	130	139	139	1.27	0.22	0.22	25.00	/	5 / 10 / 15 / 20 / 25
000225:140:x	140	149	149	1.46	0.22	0.15	25.00	/	5 / 10 / 15 / 20 / 25
000225:150:x	150	159	159	1.54	0.22	0.15	25.00	/	5 / 10 / 15 / 20 / 25
000225:152:x	152	161	161	1.56	0.22	0.15	25.00	5 / 10	5 / 10 / 15 / 20 / 25
000225:160:x	160	170	170	1.84	0.22	0.15	25.00	/	5 / 10 / 15 / 20 / 25
000225:170:x	170	180	180	1.90	0.17	0.15	25.00	/	5 / 10 / 15 / 20 / 25
000225:175:x	175	185	185	1.95	0.17	0.15	25.00	/	5 / 10 / 15 / 20 / 25
000225:180:x	180	190	190	2.01	0.17	0.15	25.00	/	5 / 10 / 15 / 20 / 25
000225:200:x	200	210	210	2.38	0.17	0.15	25.00	/	5 / 10 / 15 / 20 / 25
000225:203:x	203	214	214	2.43	0.17	0.15	25.00	5 / 10	5 / 10 / 15 / 20 / 25

Extended Article Number	Nominal Size (DN) in mm	Outer diameter in mm	Bending radius* in mm	Weight in kg/m	Operating pressure in bar	Negative pressure in bar	Max. Production length in m	Stock Lengths in m	Length (standard lengths available for order) in m
000225:225:x	225	235	235	2.69	0.11	0.07	25.00	/	5 / 10 / 15 / 20 / 25
000225:250:x	250	256	256	3.12	0.11	0.07	25.00	/	5 / 10 / 15 / 20 / 25
000225:254:x	254	260	260	3.19	0.11	0.07	25.00	/	5 / 10 / 15 / 20 / 25
000225:275:x	275	284	284	3.28	0.11	0.07	25.00	/	5 / 10 / 15 / 20 / 25
000225:300:x	300	310	310	3.38	0.10	0.07	20.00	/	5 / 10 / 15 / 20
000225:315:x	315	325	325	3.50	0.10	0.07	20.00	/	5 / 10 / 15 / 20
000225:325:x	325	335	335	3.59	0.10	0.07	20.00	/	5 / 10 / 15 / 20
000225:350:x	350	360	360	3.80	0.05	0.07	20.00	/	5 / 10 / 15 / 20
000225:400:x	400	411	410	4.70	0.05	0.05	20.00	/	5 / 10 / 15 / 20
000225:450:x	450	461	460	5.34	0.05	0.05	20.00	/	5 / 10 / 15 / 20
000225:500:x	500	511	510	6.02	0.05	0.05	20.00	/	5 / 10 / 15 / 20

All data refer to a medium and ambient temperature of +20°C.
Specification of the bending radius related to the inside of the hose bend
Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

Suitable for the product



Hose connector
Sheet steel connector for extending, connecting and joining light to medium-weight hoses



Hose Reducer, symmetrical
Hose reducer for extending, connecting and joining light to medium weight hoses



Master-Grip Hose Clamp, screwable
Special clamp for fastening light and medium-weight, right-handed spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO




Master-Grip Hose Clamp, screwable, Steel quality W4, stainless steel 1.4301
Special clamp for fastening light and medium-weight, right-handed spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO



Master-Grip Quick-Fix Clamp
Special clamp for fastening light and medium-weight, right-hand spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO



Heat Shrink Cuff
Heat shrink sleeve for easy connection and sealing of hoses



Individual consultation

We offer consultation by phone: **+49 209 97077 0**

Product requests via: <https://www.masterflex.it/>

Headquarters for your sales area

Masterflex SE

Willy-Brandt-Allee 300
45891 Gelsenkirchen
Germany