



Combiflex Clamp Ring Seal

for clamp connection according to DIN 32676 series A

Product Details

Construction / Material

- Specification of the connection solution: liquid-tight connection
- Design of the sealing ring: made of rubber
- Material of the sealing ring: NBR, material complies with the food regulations of DIN 32676 Series A

Properties

- Chemical Properties: odourless and tasteless, good resistance to chemicals
- Mechanical Properties: excellent mechanical tensile strength and tear resistance
- Colour: white

Operating Temperature

- Temperature Range: -25 to 120 °C
- short-term maximum temperature: peaks to 150 °C

Article Variants

Article number	DN of the hose in mm	Connection Metric in mm	Outer diameter in mm	Inner diameter in mm
002462	32	32	52,7	32,2
002465	40	40	52,7	38,2
002468	50	50	66,2	50,2
002472	65	65	93,2	66,2
002476	80	80	108,2	81,2
002480	100	100	121,2	100,2
002483	125	125	155,0	125,2
002485	150	150	183,0	150,2


Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).



Individual consultation

We offer consultation by phone: **+49 209 97077 0**

Product requests via: <https://www.masterflex.it/>

Headquarters for your sales area

Masterflex SE

Willy-Brandt-Allee 300
45891 Gelsenkirchen
Germany